

POLYPROPYLENE SEATS TP SPORT

REF. TP SPORT B-94 SG

DESCRIPTION

Mono bloc seat, self-bearing shell seat moulded by injection, with 60 mm back height over grandstand installation, 310 mm wide and 420mm deep.

Shiny surface sealed around the whole of perimeter to prevent dirt from accumulating inside the seat, which makes it easy to clean. Fixed in a two central anchoring points over grandstand and with central drainage

TECHNICAL CHARACTERISTICS

- Light Resistance Additive anti UV DIN 54003
- Anti-slide ridding on the seat
- Seat numbering and flame-retardance treatment (optional)
- 100% Recyclable, HD High-quality Polypropylene.
- Fire behaviour classification M3 (M2, optional) UNE 23727.
- Bending strength according to standard DIN 53455
- CHARPY impact resistance according to norm: :DIN 53453
- Hardness according to norm ISO868 :(65 Shore D).
- Traction resistance according to norm: UNE EN ISO 527 parte 1,2 y 3 (20N/mm)
- Elongation at break: (VN50mm/min) 600%.
- DIN 54003 (1-8) results 8 (excellent) in photometric scale additivities for raw materials compliance with: resolution 4/11/1982 Spanish Ministry of Health resolution AP (89) from the European Congress Spanish norm: UNE 93-011-83/ part III European norm EN 71, part 3 legislative act from 24/04/1997, nº11/1997, chapter V, article 13, which stablishes the maximum concentration of Lead, Cadmium, Mercury and Hexavalent Chromium directive 94/62/CE of the European department and the European Council 20/12/1994.



